



OVAC

Double-Drawer Series

OLEC's OVAC Double Drawer-Series exposure systems offer the fastest exposure of printing plates, proofs, and films available. Parallel frame operation increases productivity while its high resolution, sharp image, and excellent collimation guarantee the finest possible image. Designed for quick change inserts, tiling, step-and-repeat, or other integrated registration applications.

FEATURES

- *Semi-automated exposure frame system with two frames for parallel loading and exposing*
- *High productivity for films, plates, and proofing*
- *Selectable power ranging from 1000 W to 8000 W*
- *Easy operation, one-button control*
- *Motor-driven double drawers*
- *High resolution, sharp image, adjustable lamp height*
- *Modular design + built-in diagnostics*
- *Microprocessor-controlled for precise, repeatable exposures*
- *Low maintenance cost and long lamp life through servo-cooling and service-free shutters*
- *Light-tight construction*
- *Disassembles to fit through standard door (except OV 33HD)*
- *Made in the USA*

*Two Exposure
Frames in One*

*Parallel Operation
for High Productivity*

High Resolution

Built-in Registration

Easy to Use



SPECIFICATIONS



OV 33HD

SPECIFICATIONS	OV 33HD-23	OV 33HD-35	OV 33HD-53	Units
Exposure area	25 x 33 635 x 838	25 x 33 635 x 838	25 x 33 635 x 838	inch mm
Light Output	high 2300 medium 1600 low 1000	3500 2000 1000	5000 2000 1000	watt watt watt
Input voltage	208/240	208/240	208/240	vac
Maximum current	13	24	38	amp
Size	48.5 x 89 x 72 1232 x 2261 x 1829	48.5 x 89 x 72 1232 x 2261 x 1829	48.5 x 89 x 72 1232 x 2261 x 1829	inch mm
Shipping weight	1290 585	1290 585	1300 589	lb kg

• For international requirements call OLEC



OV 45HD

SPECIFICATIONS	OV 45HD-23	OV 45HD-35	OV 45HD-53	OV 45HD-83	Units
Exposure area	35 x 45 889 x 1143	35 x 45 889 x 1143	35 x 45 889 x 1143	35 x 45 889 x 1143	inch mm
Light Output	high 2300 medium 1600 low 1000	3500 2000 1000	5000 2000 1000	8000 3500 2000	watt watt watt
Input voltage	208/240	208/240	208/240	208/240	vac
Maximum current	21	25	38	50	amp
Size	61 x 95 x 79 1549 x 2413 x 2006	61 x 95 x 79 1549 x 2413 x 2006	61 x 95 x 79 1549 x 2413 x 2006	61 x 95 x 79 1549 x 2413 x 2006	inch mm
Shipping weight	1450 657	1490 675	1500 680	1600 725	lb kg

• For international requirements call OLEC



OV 60HD

SPECIFICATIONS	OV 60HD-53	OV 60HD-83	Units
Exposure area	48 x 60 1219 x 1524	48 x 60 1219 x 1524	inch mm
Light Output	high 5000 medium 2000 low 1000	8000 4000 2000	watt watt watt
Input voltage	208/240	208/240	vac
Maximum current	40	50	amp
Size	84 x 127 x 91 2134 x 3226 x 2311	84 x 127 x 91 2134 x 3226 x 2311	inch mm
Shipping weight	2000 910	2000 910	lb kg

• For international requirements call OLEC



1850 E. St. Andrew Place, Santa Ana, CA 92705, USA
 Phone 714 258 5600 • Fax 714 258 5601
 Email info@olec.com • www.olec.com